



سن لوب لوبر كنتس اندستري ذ.م.م

SUNLUBE LUBRICANTS INDUSTRY LLC

TECHNICAL DATA SHEET

SYNTHETIC PETROL ENGINE OIL

Sunlube Synthetic Petrol engine oils specially designed and formulated to exceed the latest ILSAC GF-6/API SN CF specifications with highly improved fuel efficiency performance. It offers superb cold start protection & therefore, reduces engine wear & tear significantly. The special additives contribute to a significant reduction in engine noise.

BENEFITS:

- Perfectly adapted for cold starting in extreme weather conditions and ensures good protection of mechanical parts at high temperatures as well.
- Exceptional fluidity, this oil reduces friction and therefore creates significant fuel saving.
- Contains detergent and dispersive additives that keep the engine clean and thus preserve its power.
- Antioxidant additives help for extra-long drain intervals.
- Anti-wear additives protect the engine's most sensitive parts.

PERFORMANCE STANDARDS:

- API: SN/CF
- ILSAC: GF-6/GF-5
- ACEA: A3/B4

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		10W-20
Density @ 15°C	g/cm ³	ASTM D-4052	0.854
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	50.85
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	8.5
Viscosity Index	-	ASTM D-2270	144
Flash Point	°C	ASTM D-92	230
Pour Point	°C	ASTM D-97	-36
TBN	mg KOH/g	ASTM D-2896	8.5
CCS Viscosity	cP	ASTM D-5293	5600 (-25)

V.07-2025

PO.Box: 35746, Ras Al Khaimah, U.A.E

Tel: +971 7 2434 761

+971 7 2442 659

Email : inquiry@sunlube.ae

www.sunlube.ae

ص.ب : ٣٥٧٤٦، رأس الخيمة ا.ع.م

تليفون : +٩٧١ ٧٢٤٣٤٧٦١

+٩٧١ ٧٢٤٤٢٦٥٩