TECHNICAL DATA SHEET

SYNTHETIC PETROL ENGINE OIL

Sunlube Synthetic Petrol engine oils specially designed and formulated to exceed the latest ILSAC GF-6/API SN CF specifications with highly improved fuel efficiency performance. It offers superb cold start protection & therefore, reduces engine wear & tear significantly. The special additives contribute to a significant reduction in engine noise.

BENEFITS:

- Perfectly adapted for cold starting in extreme weather conditions and ensures good protection of mechanical parts at high temperatures as well.
- Exceptional fluidity, this oil reduces friction and therefore creates significant fuel saving.
- Contains detergent and dispersive additives that keep the engine clean and thus preserve its power.
- Antioxidant additives help for extra-long drain intervals.
- Anti-wear additives protect the engine's most sensitive parts.

PERFORMANCE STANDARDS:

API: SN/CF

ILSAC: GF-6/GF-5ACEA: A3/B4

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		10W-40
Density @ 15°C	g/cm ³	ASTM D-4052	0.852
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	99.4
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	14.8
Viscosity Index	-	ASTM D-2270	159
Flash Point	°C	ASTM D-92	234
Pour Point	°C	ASTM D-97	-36
TBN	mg KOH/g	ASTM D-2896	8.5
CCS Viscosity	cP	ASTM D-5293	5300 (-25)

V.07-2025

ص.ب : ۲۰۷۶ م. رأس الخيمة ل.ع.م Tel: +971 7 2434 761 +971 7 2442 659 Email : inquiry@sunlube.ae www.sunlube.ae h971 7 2442 659