TECHNICAL DATA SHEET

SYNTHETIC PETROL ENGINE OIL

Sunlube semi synthetic lubricants formulated from a blend of selected mineral oils, synthetic base stocks and high-quality additive technology for use in passenger cars and light truck gasoline engines and passenger car diesel engines under all operating conditions

BENEFITS:

- Blended with high quality of base stocks and additives which provide excellent oxidation resistance.
- Ensures good engine cleanliness, reducing particle accumulation in the motor via efficient dispersant
- Long-term wear protection of engine parts (distribution, ring, plunger and liner) increasing engine life

PERFORMANCE STANDARDS:

API: SL/CFILSAC: GF-5

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		20W-40
Density @ 15°C	g/cm ³	ASTM D-4052	0.892
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	128
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	15
Viscosity Index	-	ASTM D-2270	120
Flash Point	°C	ASTM D-92	240
Pour Point	°C	ASTM D-97	-24
TBN	mg KOH/g	ASTM D-2896	7.5
CCS Viscosity	cР	ASTM D-5293	6800 (-15)

V.07-2025

ص.ب : ۲۰۷۶ م. رأس الخيمة ال.ع.م Tel: +971 7 2434 761 +971 7 2442 659 Email : inquiry@sunlube.ae www.sunlube.ae h٩٧١٧٢٤٣٤٧٦٦ و١٩٩١