



سن لوب لوبر كنتس اندستري ذ.م.م

SUNLUBE LUBRICANTS INDUSTRY LLC

TECHNICAL DATA SHEET

SYNTHETIC PETROL ENGINE OIL

Sunlube semi synthetic lubricants formulated from a blend of selected mineral oils, synthetic base stocks and high-quality additive technology for use in passenger cars and light truck gasoline engines and passenger car diesel engines under all operating conditions

BENEFITS:

- Blended with high quality of base stocks and additives which provide excellent oxidation resistance.
- Ensures good engine cleanliness, reducing particle accumulation in the motor via efficient dispersant
- Long-term wear protection of engine parts (distribution, ring, plunger and liner) increasing engine life

PERFORMANCE STANDARDS:

- API: SL/CF
- ILSAC: GF-5

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		20W-60
Density @ 15°C	g/cm ³	ASTM D-4052	0.893
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	210
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	23
Viscosity Index	-	ASTM D-2270	135
Flash Point	°C	ASTM D-92	242
Pour Point	°C	ASTM D-97	-21
TBN	mg KOH/g	ASTM D-2896	7.5
CCS Viscosity	cP	ASTM D-5293	8900 (-15)

V.07-2025