



سن لوب لوبر كنتس اندستري ذ.م.م

SUNLUBE LUBRICANTS INDUSTRY LLC

TECHNICAL DATA SHEET

MOTORCYCLE OILS

Sunlube 4T is a series of premium, synthetic-blend, shear-stable, multigrade, multifunctional lubricants developed specifically for gasoline motorcycle engines, clutches and gearboxes working under severe duty conditions. Its high frictional properties guarantee the clutch engagement for enhanced acceleration. Synthetic-blend formulation and carefully selected additives provide excellent protection against wear, deposits formation and thermal breakdown, keeping the performance throughout the full oil service life. It is highly recommended for use in four-stroke gasoline motorcycle Engine, Clutch and Gear (ECG) applications such as Honda, Suzuki, Kawasaki, Yamaha, Bajaj and other motorcycles that require the specifications below.

BENEFITS:

- Excellent oxidation stability under exposure to high operating temperature
- Optimized frictional properties that deliver smooth clutch operation
- Protects vital gear & clutch components to maximize their service life
- Provides exceptional protection against rust and keeps engine parts protected from wear
- Provides long drain intervals
- Wide operating conditions from mild to severe

PERFORMANCE STANDARDS:

- JASO MA/MA2
- API SN

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		15W-50
Density @ 15°C	g/cm ³	ASTM D-4052	0.865
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	134
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	18
Viscosity Index	-	ASTM D-2270	150
Flash Point	°C	ASTM D-92	230
Pour Point	°C	ASTM D-97	-27
TBN	Mg KOH/g	ASTM D-2896	7
CCS Viscosity	cP	ASTM D-5293	6100 (-20)

V.07-2025