



سن لوب لوبر كنتس اندستري ذ.م.م

**SUNLUBE LUBRICANTS INDUSTRY LLC**

## **TECHNICAL DATA SHEET**

### **AUTOMATIC TRANSMISSION FLUID**

Sunlube ATF Dexron III-H is a high performance, multifunctional, automatic transmission fluid formulated with full synthetic base oils and specially selected additives that provide optimal friction properties as well as protection against corrosion, wear, sludge, deposits and lubricant oxidation. It is suitable for passenger car and commercial vehicle automatic transmission, hydraulic systems of mobile and off-high way equipment and industrial equipment applications that required the following specifications

#### **BENEFITS:**

- Optimal friction properties provide smooth shifting and trouble-free operations
- Compatible with all types of rubbers, elastomers and metals and providing protection against wear and leakage
- Excellent low-temperature fluidity
- Excellent oxidation resistance resulting in cleaner transmissions
- Good shear stability

#### **PERFORMANCE STANDARDS:**

- GM Dexron® III-H
- Allison C-4, TES 389
- Ford Mercon®

#### **TYPICAL PROPERTIES:**

Properties	Unit	Test Method	
Grade	-		<b>Dexron III-H</b>
Density @ 15°C	g/cm <sup>3</sup>	ASTM D-4052	0.854
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /S	ASTM D-445	34.3
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /S	ASTM D-445	7.3
Viscosity Index	-	ASTM D-2270	185
Flash Point	°C	ASTM D-92	200
Pour Point	°C	ASTM D-97	-42
Colour	-	Visual	Red

V.07-2025

PO.Box: 35746,Ras Al Khaimah,U.A.E

Tel: +971 7 2434 761

+971 7 2442 659

Email : [inquiry@sunlube.ae](mailto:inquiry@sunlube.ae)

[www.sunlube.ae](http://www.sunlube.ae)

ص.ب : ٣٥٧٤٦ ، رأس الخيمة ا.ع.م

تليفون : +٩٧١ ٧٢٤٣٤٧٦١

+٩٧١ ٧٢٤٤٢٦٥٩