



سن لوب لوبر كنتس اندستري ذ.م.م

**SUNLUBE LUBRICANTS INDUSTRY LLC**

## **TECHNICAL DATA SHEET**

### **AUTOMATIC TRANSMISSION FLUID**

Sunlube Dexron II-D is multifunctional, automatic transmission fluid formulated with high quality base oils and specially selected additives that provide protection against corrosion, wear and sludge formation. It is suitable for automatic transmission and power steering used in heavy trucks and off-road vehicles and older passenger cars. It can also be used in powershift and industrial torque convertors and other hydraulic systems that require a GM Dexron II-D or GM Type 'A' Suffix 'A' performance levels.

### **BENEFITS:**

- Good oxidation resistance
- Good seal compatibility
- Protection against corrosion, wear and sludge formation
- Excellent low-temperature fluidity
- Good shear stability

### **PERFORMANCE STANDARDS:**

- GM Type 'A' Suffix 'A' (TASA)
- GM Dexron® II-D
- Allison C-4

### **TYPICAL PROPERTIES:**

Properties	Unit	Test Method	
Grade	-		<b>Dexron II-D</b>
Density @ 15°C	g/cm <sup>3</sup>	ASTM D-4052	0.846
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /S	ASTM D-445	38.9
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /S	ASTM D-445	7.4
Viscosity Index	-	ASTM D-2270	160
Flash Point	°C	ASTM D-92	198
Pour Point	°C	ASTM D-97	-45
Colour	-	Visual	Red

V.07-2025

PO.Box: 35746, Ras Al Khaimah, U.A.E

Tel: +971 7 2434 761  
+971 7 2442 659

Email : [inquiry@sunlube.ae](mailto:inquiry@sunlube.ae)

[www.sunlube.ae](http://www.sunlube.ae)

ص.ب : ٣٥٧٤٦، رأس الخيمة ا.ع.م

تليفون: +٩٧١ ٧٢٤٣٤٧٦١  
+٩٧١ ٧٢٤٤٢٦٥٩