



سن لوب لوبر كنتس اندستري ذ.م.م

SUNLUBE LUBRICANTS INDUSTRY LLC

TECHNICAL DATA SHEET

MOTORCYCLE OILS

Sunlube 2T Engine Oil is an-advanced technology top graded 2-stroke motor oil formulated with fully synthetic base oil and low-ash additive package to release maximum power with minimum drag. It is recommended for high performance motorcycles, especially for road use. It is also recommended for smaller engines fitted in Scooters, Lawn mowers and other small equipment. It should be added with gasoline in the ratio recommended by the equipment manufacturer.

BENEFITS:

- The superior combustion characteristics of the special blend of unique fully synthetic oil and additives significantly reduce visible smoke in exhaust emission providing environmentally friendly lubricants.
- Controls Combustion Chamber and Spark Plug deposit build-up
- Excellent miscibility with Gasoline.
- Keeps pistons, rings, plugs and exhaust ports clean

PERFORMANCE STANDARDS:

- JASO FD
- API TC
- ISO L-EGD

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		2T
Density @ 15°C	g/cm ³	ASTM D-4052	0.872
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	TBR
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	9.0
Viscosity Index	-	ASTM D-2270	TBR
Flash Point	°C	ASTM D-92	70
Pour Point	°C	ASTM D-97	-24
Colour	-	ASTM D-1500	2.0

V.07-2025